

OUTDOOR 'WIND-RATED' HOARDING CONFIGURATIONS

- Temporary Works forum (TWf) compliant
- Completely free-standing – no fixings or ground penetrations required and no property damage caused
- Modular System offers multiple height options up to 4mH or wind speed capabilities up to 112Mph
- Both Single and Double stack configurations available to meet site-specific wind requirements
- Single Stack option has a footprint of only 46cm deep
- Double Stack option has a footprint of only 92cm deep
- Proprietary 'Support Post' available to support both options



DOUBLE STACK CONFIGURATION

Example shown:
3.6mH with
Double stacks of
8+8 Counterweights
with only a 92cm
deep footprint

OUTDOOR HOARDINGS – DOUBLE STACK – 'WEIGHT / HEIGHT/ WIND SPEED' EXAMPLES

FREE-STANDING HOARDING OPTIONS FOR **DOUBLE STACK OF COUNTERWEIGHTS @ 1.2MW INTERVALS**

SOLID PANEL HEIGHT – MAX (H)	TIMBER STUD REQUIRED	WIND SPEED 15M/S (33.5MPH)	WIND SPEED 19M/S (42.5MPH)	WIND SPEED 21M/S (47MPH)	WIND SPEED 23M/S (51.5MPH)	WIND SPEED 26M/S (58.2MPH)	WIND SPEED 29M/S (65MPH)
1.8m	97 x 47 C24	From 3+3	From 3+3	From 3+3	From 3+3	From 3+3	N/A
2.4m	97 x 47 C24	From 3+3	From 3+3	From 3+3	From 4+4	From 4+4	From 5+5
3m	97 x 47 C24	From 3+3	From 4+4	From 5+5	From 6+6	From 7+7	From 9+9
3.6m	97 x 47 C24	From 4+4	From 6+6	From 8+8	From 9+9	From 11+11	N/A
4m	97 x 47 C24	From 5+5	From 8+8	From 10+10	From 12+12	N/A	N/A

FREE-STANDING HOARDING OPTIONS FOR **SINGLE STACK OF COUNTERWEIGHTS @ 0.6MW INTERVALS**

SOLID PANEL HEIGHT – MAX (H)	TIMBER STUD REQUIRED	WIND SPEED 15M/S (33.5MPH)	WIND SPEED 19M/S (42.5MPH)	WIND SPEED 21M/S (47MPH)	WIND SPEED 23M/S (51.5MPH)	WIND SPEED 26M/S (58.2MPH)	WIND SPEED 29M/S (65MPH)
1.8m	97 x 47 C24	From 3+3	From 3+3	From 3+3	From 3+3	From 3+3	From 3+3
2.4m	97 x 47 C24	From 3+3	From 3+3	From 3+3	From 3+3	From 3+3	From 3+3
3m	97 x 47 C24	From 3+3	From 3+3	From 3+3	From 3+3	From 4+4	From 5+5
3.6m	97 x 47 C24	From 3+3	From 3+3	From 4+4	From 5+5	From 6+6	From 7+7
4m	97 x 47 C24	From 3+3	From 4+4	From 5+5	From 6+6	From 6+6	From 9+9

Multiple Factors Apply for Calculations - See 'Lomax System Outdoor Configurator' for full range of options

FOR MORE INFO PLEASE CONTACT: chris.wood@hoardtek.co.uk
0345 257 0707

HOARDTEK